

```
acl viera_lan src 192.168.10.0/24

acl SSL_ports port 443
acl Safe_ports port 80      # http
acl Safe_ports port 21     # ftp
acl Safe_ports port 22     # ssh
acl Safe_ports port 53     # dns
acl Safe_ports port 443    # https
acl Safe_ports port 70     # gopher
acl Safe_ports port 210    # wais
acl Safe_ports port 1025-65535 # unregistered ports
acl Safe_ports port 280    # http-mgmt
acl Safe_ports port 488    # gss-http
acl Safe_ports port 591    # filemaker
acl Safe_ports port 777    # multiling http
acl CONNECT method CONNECT

http_access deny !Safe_ports
http_access deny CONNECT !SSL_ports
http_access allow localhost manager
http_access deny manager
http_access deny to_localhost
http_access allow viera_lan
http_access allow localhost
http_access deny all
http_port 192.168.10.2:3128
hosts_file /etc/hosts
dns_v4_first on
dns_nameservers 192.168.10.1
half_closed_clients off
```

error_default_language es
error_directory /usr/share/squid/errors/es-hn
httpd_suppress_version_string on
uri_whitespace strip

cache_dir aufs /var/spool/squid 5024 16 256
coredump_dir /var/spool/squid

refresh_pattern ^ftp:	1440	20%	10080
refresh_pattern ^gopher:	1440	0%	1440
refresh_pattern -i (/cgi-bin/ \?)	0	0%	0
refresh_pattern .	0	20%	4320

cache_mem 1024 MB
cache_swap_high 98
cache_swap_low 90
cache allow all
forwarded_for off
cache_effective_user squid
cache_effective_group wbpriv
maximum_object_size 4 MB
minimum_object_size 0 KB
request_body_max_size 0 KB
memory_replacement_policy heap GDSF
cache_replacement_policy heap LFUDA
maximum_object_size_in_memory 256 MB
visible_hostname proxy.viera.lan
cache_mgr robertom@viera.lan

access_log /var/log/squid/access.log

cache_log /var/log/squid/cache.log

mime_table /etc/squid/mime.conf

log_mime_hdrs on

pid_filename /run/squid.pid

cache_store_log /var/log/squid/store.log